Product Data Sheet Item No. 2352-030-06

Cargo Net 3.00 x 3.50 m

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Maii: office@safetynet365.com Web: www.safetynet365.com









п	F	C L	ЛL	110	$^{\wedge}$	1		۸Т	٠,
		. , г	ווד	""	JΑ		1)/	4 I	A

Available Colors	black				
Dimensions	9' 10" x 11' 6"				
Material	high tenacity polypropylene, knotless				
Material Diameter	Ø 0.07"				
Mesh Size	1.2" x 1.2"				
Pose of Meshes	quadratic (square)				
Mesh Connection	knotless braid				
Edge Design	reinforced selvage cord of approx. 14"				
Shock Cord	incl. pulled in shock cord, Ø 14"				
Max. Tensile Strength of a Mesh	130 lbf				
Tensile Breaking Force Referred to Density	7.0 cN/den				
Breaking Elongation of Filament	15%				
Standards and Rules	VDI standard 2700				
Certificate	DEKRA certificate 201023818, Oeko-Tex® certificate 12.0.02466				
Continuous Operating Temperature	-40 to +175 °F				
Melting Point	329 °F				
Washing Temperature (max.)	80 °F				
Yarn Moisture Regain	0%				
Tensile Strength Reduction Because Of Moisture	0%				
Resistance to Weak/Strong Acids	very good/good				
Resistance to Weak/Strong Alkalis	good/not good				
Resistance to Organic Solvents	good				
Resistance to Benzine and Greases	very good				
Bending Strength & Abrasion Resistance	good				

Weather-Resistance	good
UV-Resistance	300 kly
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	56081930
Area Density	2.50 oz/yd²
Total Weight	3.09 lb