


Product Data Sheet Item No. 924R

PVC-Coated Polyester Netting 1.15 x 130.00 m

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 436 96 40
Mail: office@safetynet365.com
Web: www.safetynet365.com



TECHNICAL DATA

Available Colors	black
Dimensions	3' 9" x 426'
Material	polyester, coated with PVC
Material Diameter	Ø 0.16"
Mesh Size	1.6" x 1.6"
Pose of Meshes	quadratic (square)
Edge Design	without edge
Continuous Operating Temperature	-10 to +140 °F
Melting Point	356 °F
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalis	good/not good
Resistance to Organic Solvents	not good
Resistance to Benzine and Greases	very good
Bending Strength & Abrasion Resistance	very good
Weather-Resistance	good
UV-Resistance	300 kly
Elasticity After Years of Climatic Influences	good long-term flexibility, no elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	no contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity

Customs Tariff No.	56081930
Area Density	14.15 oz/yd ²
Total Weight	157.66 lb