

**Product Data Sheet Item No. SN-01651-025**  
**Luggage Net with Steel Frame, Close-meshed**

Schutznetze24 GmbH  
Weyerberg 5, DE-35614 Aßlar-Berghausen  
Phone: +49 (0) 6443 - 436 96 40  
Mail: [office@safetynet365.com](mailto:office@safetynet365.com)  
Web: [www.safetynet365.com](http://www.safetynet365.com)



**STANDARD  
100**  
12.0.02466  
Hohenstein HTTI



**TECHNICAL DATA**

Material	polyester, knotless, powder-coated steel frame, polyamide screw-on brackets
Material Diameter	Ø 0.10"
Mesh Size	1.0" x 1.0"
Pose of Meshes	rhombic (diamond mesh)
Mesh Connection	knotless braid
Edge Design	adjustable screw-on brackets with screw holes (Ø 164"), steel frame (Ø 316", black powder-coated), shock cord (Ø 316", latex core, polyester cover) attached to the upper edge
Certificate	Oeko-Tex®; certificate 1904052
Continuous Operating Temperature	-40 to +212 °F
Melting Point	500 °F
Yarn Moisture Regain	0.5 to 2.0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalis	good/good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	good
Bending Strength & Abrasion Resistance	good
Weather-Resistance	good
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction

Behavior in High Heat / Fire	melting
Included Parts	luggage net on steel frame, 4 screw-on brackets
Customs Tariff No.	56081930
Total Weight	0.00 lb