



STANDARD  
100  
12.0.02466  
Hohenstein HTTI

## TECHNICAL DATA

Material	polyester, knotless, flexible, with internal elasticated yarn, polyamide screw-on brackets
Material Diameter	Ø 0.10"
Mesh Size	0.8" x 0.8"
Pose of Meshes	rhombic (diamond mesh)
Mesh Connection	knotless braid
Edge Design	adjustable screw-on brackets with screw holes (Ø 164"), shock cord (Ø 316", latex core, polyester cover), threaded all the way round
Certificate	Oeko-Tex®; certificate 1904052
Continuous Operating Temperature	-40 to +212 °F
Melting Point	500 °F
Yarn Moisture Regain	0.5 to 2.0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalies	good/good
Resistance to Organic Solvents	good
Resistance to Benzene and Greases	good
Bending Strength & Abrasion Resistance	good
Weather-Resistance	good
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction

<b>Behavior in High Heat / Fire</b>	melting
<b>Included Parts</b>	luggage net, rubber cord, 4 or 5 screw-on brackets (depending on size), fastener for rubber cord, comes with an additional hook for the 40" version
<b>Customs Tariff No.</b>	56081930
<b>Total Weight</b>	0.00 lb