



TECHNICAL DATA

Available Colors	green
Dimensions	6' 7" x 9' 10"
Material	high tenacity polypropylene, knotless
Material Diameter	Ø 0.10"
Mesh Size	1.8" x 1.8"
Pose of Meshes	rhombic (diamond mesh)
Mesh Connection	knotless braid
Edge Design	borders on long sides with elastic edge stitch (sewn shock cord)
Max. Tensile Strength of a Mesh	200 lbf
Tensile Breaking Force Referred to Density	7.0 cN/den
Breaking Elongation of Filament	15%
Standards and Rules	VDI standard 2700
Certificate	Oeko-Tex®; certificate 12.0.02466
Continuous Operating Temperature	-40 to +175 °F
Melting Point	329 °F
Washing Temperature (max.)	80 °F
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	very good/good
Resistance to Weak/Strong Alkalies	good/not good
Resistance to Organic Solvents	good
Resistance to Benzene and Greases	very good
Bending Strength & Abrasion Resistance	good
Weather-Resistance	good

UV-Resistance	300 kly
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	56081930
Area Density	3.25 oz/yd ²
Total Weight	0.88 lb