Product Data Sheet Item No. 2343-045-01

Container Net 3.50 x 6.00 m

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Maii: office@safetynet365.com Web: www.safetynet365.com









	_		_		
TE	\sim 11		\sim $^{\wedge}$		ATA
		$I \times I \setminus I$	(A	1 1/	м и д
	\ /	1 / 1	$\overline{}$	1 / -	\sim

Available Colors	green			
Dimensions	11' 6" x 19' 8"			
Material	high tenacity polypropylene, knotless			
Material Diameter	Ø 0.09"			
Mesh Size	1.8" x 1.8"			
Pose of Meshs	quadratic (square)			
Mesh Connection	knotless braid			
Edge Design	reinforced selvage cord of approx. 14"			
Shock Cord	incl. pulled in shock cord, Ø 14"			
Max. Tensile Strength of a Mesh	180 lbf			
Tensile Breaking Force Referred to Density	7.0 cN/den			
Breaking Elongation of Filament	15%			
Standards and Rules	VDI standard 2700			
Certificate	DEKRA certificate 201125785, Oeko-Tex® certificate 12.0.02466			
Continuous Operating Temperature	-40 to +175 °F			
Melting Point	329 °F			
Washing Temperature (max.)	80 °F			
Yarn Moisture Regain	0%			
Tensile Strength Reduction Because Of Moisture	0%			
Resistance to Weak/Strong Acids	very good/good			
Resistance to Weak/Strong Alkalis	good/not good			
Resistance to Organic Solvents	good			
Resistance to Benzine and Greases	very good			
Bending Strength & Abrasion Resistance	good			

Weather-Resistance	good
UV-Resistance	300 kly
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	56081930
Area Density	2.65 oz/yd²
Total Weight	6.17 lb