


# Product Data Sheet Item No. 2062-130-04

## Lifting Net 3.30 x 3.30 m

Schutznetze24 GmbH  
Weyerberg 5, DE-35614 Aßlar-Berghausen  
Phone: +49 (0) 6443 - 436 96 40  
Mail: office@safetynet365.com  
Web: www.safetynet365.com



### TECHNICAL DATA

Available Colors	blue
Dimensions	10' 10" x 10' 10"
Material	high tenacity polypropylene, knotless
Material Diameter	Ø 0.60"
Mesh Size	5.1" x 5.1"
Pose of Meshes	rhombic (diamond mesh)
Mesh Connection	knotless braid
Edge Design	with edged rope, with two cross ropes through the net (PA Ø 0.55"), incl. loops with scuff protection on the corners
Edged Rope	nylon rope (Ø 0.55", white), all around
Max. Tensile Strength of a Mesh	1860 lbf
Breaking Elongation of Filament	15%
Payload	3.3 tn. sh.
Standards and Rules	EN 1263-1
Certificate	Oeko-Tex&reg; certificate 12.0.02466
Continuous Operating Temperature	-40 to +175 °F
Melting Point	329 °F
Washing Temperature (max.)	80 °F
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	very good/good
Resistance to Weak/Strong Alkalis	good/hot good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	very good

<b>Bending Strength &amp; Abrasion Resistance</b>	good
<b>Weather-Resistance</b>	good
<b>UV-Resistance</b>	300 kly
<b>Tensile Strength After Two Years of Climatic Influences</b>	90%
<b>Elasticity After Years of Climatic Influences</b>	good long-term flexibility, little elongation
<b>Flexibility When Used in Water</b>	stays flexible
<b>Contraction When Used in Water</b>	low contraction
<b>Contraction When Used Outside</b>	no contraction
<b>Behavior in High Heat / Fire</b>	melting
<b>Electrical Characteristics</b>	isolating, no electrical conductivity
<b>Customs Tariff No.</b>	56081930
<b>Area Density</b>	33.90 oz/yd <sup>2</sup>
<b>Total Weight</b>	34.62 lb