Product Data Sheet Item No. 209-045

Slope Stabilisation Net by the m² (Custom-Made)

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Mail: office@safetynet365.com Web: www.safetynet365.com









Material Diameter Ø 0.12" (18") Mesh Size 1.8" x 1.8" Pose of Meshes quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature 40 to +175 "F Melting Point 329 "F Washing Temperature (max.) 80 "F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Akalis good/not good Resistance to Organic Solvents good Resistance to Organic Solvents good Bending Strength & Abrasion Resistance good Weather-Resistance 9 good	TECHNICAL DATA	
Mesh Size 1.8" x 1.8" Pose of Meshes quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature 40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance 9 good	Available Colors	green, dark green, white, blue, yellow, black, anthracite, red, beige (hemp colored)
Mesh Size 1.8" x 1.8" Pose of Meshes quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature 40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Aclds very good/good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance 9 good	Material	high tenacity polypropylene, knotless
Pose of Meshes Mesh Connection knotless braid knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh Z80 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature 40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain O% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Weather-Resistance	Material Diameter	Ø 0.12" (18")
Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14* Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Weather-Resistance good	Mesh Size	1.8" x 1.8"
Edge Design reinforced selvage cord of approx. 14* Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance 9 good	Pose of Meshes	quadratic (square)
Max. Tensile Strength of a Mesh Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance	Mesh Connection	knotless braid
Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Edge Design	reinforced selvage cord of approx. 14"
Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Max. Tensile Strength of a Mesh	280 lbf
Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Tensile Breaking Force Referred to Density	7.0 cN/den
Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Breaking Elongation of Filament	15%
Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Certificate	Oeko-Tex® certificate 12.0.02466
Washing Temperature (max.) Yarn Moisture Regain O% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids Resistance to Weak/Strong Alkalis Resistance to Organic Solvents Resistance to Benzine and Greases Weather-Resistance Ogood Weather-Resistance Ogood Solvents Ogood Ogoo	Continuous Operating Temperature	-40 to +175 °F
Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Melting Point	329 °F
Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Washing Temperature (max.)	80 °F
Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Yarn Moisture Regain	0%
Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Tensile Strength Reduction Because Of Moisture	0%
Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Resistance to Weak/Strong Acids	very good/good
Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good	Resistance to Weak/Strong Alkalis	good/not good
Bending Strength & Abrasion Resistance good Weather-Resistance good	Resistance to Organic Solvents	good
Weather-Resistance good	Resistance to Benzine and Greases	very good
3	Bending Strength & Abrasion Resistance	good
IIV-Resistance 300 kly	Weather-Resistance	good
or resistance 500 kg	UV-Resistance	300 kly
Tensile Strength After Two Years of Climatic Influences 90%	Tensile Strength After Two Years of Climatic Influences	90%

Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	56081930
Area Density	4.40 oz/yd²