
## Product Data Sheet Item No. 215-045

Ball Stop Net for Hockey by the m<sup>2</sup> (Custom-Made)

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Maii: office@safetynet365.com Web: www.safetynet365.com









Available Colors green, white, blue, yellow, black, red  Material Material Material Diameter Ø 0.16"  Mesh Size 1.8" x 1.8"  Pose of Meshs quadratic (square) Mesh Connection knotless braid  Edge Design reinforced selvage cord of approx. 14"  Max. Tensile Strength of a Mesh 360 lbf  Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F  Yarn Moisture Regain 0%
Material Diameter       Ø 0.16"         Mesh Size       1.8" x 1.8"         Pose of Meshs       quadratic (square)         Mesh Connection       knotless braid         Edge Design       reinforced selvage cord of approx. 14"         Max. Tensile Strength of a Mesh       360 lbf         Tensile Breaking Force Referred to Density       7.0 cN/den         Breaking Elongation of Filament       15%         Certificate       Oeko-Tex® certificate 12.0.02466         Continuous Operating Temperature       -40 to +175 °F         Melting Point       329 °F         Washing Temperature (max.)       80 °F
Mesh Size  1.8" x 1.8"  Pose of Meshs quadratic (square)  Mesh Connection knotless braid  Edge Design reinforced selvage cord of approx. 14"  Max. Tensile Strength of a Mesh 360 lbf  Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Pose of Meshs quadratic (square)  Mesh Connection knotless braid  Edge Design reinforced selvage cord of approx. 14"  Max. Tensile Strength of a Mesh 360 lbf  Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Mesh Connection knotless braid  Edge Design reinforced selvage cord of approx. 14"  Max. Tensile Strength of a Mesh 360 lbf  Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Edge Design reinforced selvage cord of approx. 14"  Max. Tensile Strength of a Mesh 360 lbf  Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Max. Tensile Strength of a Mesh Tensile Breaking Force Referred to Density 7.0 cN/den  Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Tensile Breaking Force Referred to Density  7.0 cN/den  Breaking Elongation of Filament  15%  Certificate  Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature  -40 to +175 °F  Melting Point  329 °F  Washing Temperature (max.)  80 °F
Breaking Elongation of Filament 15%  Certificate Oeko-Tex® certificate 12.0.02466  Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Certificate       Oeko-Tex® certificate 12.0.02466         Continuous Operating Temperature       -40 to +175 °F         Melting Point       329 °F         Washing Temperature (max.)       80 °F
Continuous Operating Temperature -40 to +175 °F  Melting Point 329 °F  Washing Temperature (max.) 80 °F
Melting Point 329 °F Washing Temperature (max.) 80 °F
Washing Temperature (max.) 80 °F
Yarn Moisture Regain 0%
Tensile Strength Reduction Because Of Moisture 0%
Resistance to Weak/Strong Acids very good/good
Resistance to Weak/Strong Alkalis good/not good
Resistance to Organic Solvents good
Resistance to Benzine and Greases very good
Bending Strength & Abrasion Resistance good
Weather-Resistance good
UV-Resistance 300 kly
Tensile Strength After Two Years of Climatic Influences 90%

Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	95069990
Area Density	6.20 oz/yd²