Product Data Sheet Item No. 18041-100

Fall Safety Net 6.00 x 10.00 m (Diagonal Meshes)











| TECHNICAL DATA | |
|--|--|
| Available Colors | green |
| Dimensions | 19' 8" x 32' 10" |
| Material | high tenacity polypropylene, knotless |
| Material Diameter | Ø 0.19" (316") |
| Mesh Size | 4.0" x 4.0" |
| Pose of Meshs | rhombic (diamond mesh) |
| Mesh Connection | knotless braid |
| Edge Design | with edged rope |
| Edged Rope | polysteel rope (Ø 12", white), all around |
| Max. Tensile Strength of a Mesh | 670 lbf |
| Energy Absorption (approx.) | 5.0 kJ |
| Tensile Strength of Edged Rope | 6,700 lbf |
| Tensile Breaking Force Referred to Density | 7.0 cN/den |
| Breaking Elongation of Filament | 15% |
| Standards and Rules | BG regulation no. 179, DGUV standard 101-011, EN 1263-1 |
| Certificate | GS verification certificate 23100031, Oeko-Tex® certificate 12.0.02466 |
| Net Class | A2 |
| Safety Net System | S (rope-edged safety net) |
| Regular Inspection Interval | 12 months |
| Number of Test Meshes | 3 pcs. |
| Continuous Operating Temperature | -40 to +175 °F |
| Melting Point | 329 °F |
| Washing Temperature (max.) | 80 °F |

| 0% |
|---|
| 0% |
| very good/good |
| good/not good |
| good |
| very good |
| good |
| good |
| 300 kly |
| 90% |
| good long-term flexibility, little elongation |
| stays flexible |
| low contraction |
| no contraction |
| melting |
| isolating, no electrical conductivity |
| 56081930 |
| 8.10 oz/yd² |
| 27.23 lb |
| |