

# Product Data Sheet Item No. 59400K-320-03

Belt Strap Cargo Net 1525 x 3025 mm -  
Complete Set

Schutzenetz24 GmbH  
Weyerberg 5, DE-35614 Aßlar-Berghausen  
Phone: +49 (0) 6443 - 436 96 40  
Mail: office@safetynet365.com  
Web: www.safetynet365.com



## TECHNICAL DATA

Available Colors	orange
Dimensions	5' x 10'
Material	high tenacity polypropylene, knotless, polyester
Material Diameter	Ø 0.09" (cover net)
Strap Width	1.00"
Mesh Size	0.8" x 0.8", 12.0" x 12.0"
Pose of Meshes	quadratic (square)
Mesh Connection	seamed
Edge Design	with edged polyester tape (approx. 1" wide), with D rings
Eyelets	steel D rings (inner diameter approx. 30x35 mm, 6 mm strong), in webbing loop, adds in total approx. 60 mm
Permissible Tensile Force	900 lbf (lashing point), 2,900 lbf (net total)
Breaking Elongation of Filament	10%
Standards and Rules	EN 12195-2, VDI standard 2700
Certificate	GS verification certificate
Continuous Operating Temperature	-40 to +175 °F
Melting Point	329 °F
Washing Temperature (max.)	80 °F
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	very good/good
Resistance to Weak/Strong Alkalies	good/not good
Resistance to Organic Solvents	good
Resistance to Benzene and Greases	very good

<b>Bending Strength &amp; Abrasion Resistance</b>	good
<b>Tensile Strength After Two Years of Climatic Influences</b>	90%
<b>Elasticity After Years of Climatic Influences</b>	good long-term flexibility, little elongation
<b>Flexibility When Used in Water</b>	stays flexible
<b>Contraction When Used in Water</b>	low contraction
<b>Contraction When Used Outside</b>	no contraction
<b>Behavior in High Heat / Fire</b>	melting
<b>Electrical Characteristics</b>	isolating, no electrical conductivity
<b>Included Parts</b>	cargo net incl. 6 tension belts (two-piece load restraint assembly, max. tensile force: 2200 lbf, length: 6.5')
<b>Customs Tariff No.</b>	63079010
<b>Total Weight</b>	11.25 lb