Product Data Sheet Item No. 209T045-4F/2FSoccer Goal Net by the m² (Custom-Made), Colorful

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Mail: office@safetynet365.com Web: www.safetynet365.com









Available Colors red/green/yellow/blue, green/white, blue/white, red/white Material high tenacity polypropylene, knotless Material Diameter 0 0.12° (18°) Mesh Size 1.8° x 1.8° Pose of Meshs quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14° Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Cortificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature 40 to +175 °F Washing Temperature (max.) 30° F Varn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Aklalis 9cod/logood Resistance to Weak/Strong Aklalis 9cod Resistance to Denzine and Greases yery good Bending Strength & Abrasion Resistance 9cod Uv-Resistance 3cod Uv-Resistance 3cod kl	TECHNICAL DATA	
Material Diameter Ø 0.12° (18°) Mesh Size 1.8° x 1.8° Pose of Meshs quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14° Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Aklalis good/not good Resistance to Weak/Strong Aklalis good/not good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Available Colors	red/green/yellow/blue, green/white, blue/white, red/white
Mesh Size 1.8" x 1.8" Pose of Meshs quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02468 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Material	high tenacity polypropylene, knotless
Pose of Meshs Quadratic (square) Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14" Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 80% Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Material Diameter	Ø 0.12" (18")
Mesh Connection knotless braid Edge Design reinforced selvage cord of approx. 14* Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good Resistance to Organic Solvents good Bending Strength & Abrasion Resistance good Weather-Resistance good Weather-Resistance 300 kly	Mesh Size	1.8" x 1.8"
Edge Design reinforced selvage cord of approx. 14° Max. Tensile Strength of a Mesh 280 lbf Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Pose of Meshs	quadratic (square)
Max. Tensile Strength of a Mesh Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Mesh Connection	knotless braid
Tensile Breaking Force Referred to Density 7.0 cN/den Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain O% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Edge Design	reinforced selvage cord of approx. 14"
Breaking Elongation of Filament 15% Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Max. Tensile Strength of a Mesh	280 lbf
Certificate Oeko-Tex® certificate 12.0.02466 Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Tensile Breaking Force Referred to Density	7.0 cN/den
Continuous Operating Temperature -40 to +175 °F Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Breaking Elongation of Filament	15%
Melting Point 329 °F Washing Temperature (max.) 80 °F Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Certificate	Oeko-Tex® certificate 12.0.02466
Washing Temperature (max.) Yarn Moisture Regain O% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Continuous Operating Temperature	-40 to +175 °F
Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Melting Point	329 °F
Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Washing Temperature (max.)	80 °F
Resistance to Weak/Strong Acids Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Yarn Moisture Regain	0%
Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Tensile Strength Reduction Because Of Moisture	0%
Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Resistance to Weak/Strong Acids	very good/good
Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Resistance to Weak/Strong Alkalis	good/not good
Bending Strength & Abrasion Resistance good Weather-Resistance good UV-Resistance 300 kly	Resistance to Organic Solvents	good
Weather-Resistance good UV-Resistance 300 kly	Resistance to Benzine and Greases	very good
UV-Resistance 300 kly	Bending Strength & Abrasion Resistance	good
,	Weather-Resistance	good
Tensile Strength After Two Years of Climatic Influences 90%	UV-Resistance	300 kly
	Tensile Strength After Two Years of Climatic Influences	90%

Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Included Parts	goal net incl. tension cord (goal frame and net holders are not incuded)
Customs Tariff No.	95069990
Area Density	4.40 oz/yd²